

Package: minidown (via r-universe)

September 12, 2024

Type Package

Title Create Simple Yet Powerful HTML Documents with Light Weight CSS Frameworks

Version 0.4.0

Maintainer Atsushi Yasumoto <atusy.rpkg@gmail.com>

Description Create minimal, responsive, and style-agnostic HTML documents with the lightweight CSS frameworks such as 'sakura', 'Water.css', and 'spcss'. Powerful features include table of contents floating as a sidebar, folding codes and results, and more.

URL <https://minidown.atusy.net>, <https://github.com/atusy/minidown>

BugReports <https://github.com/atusy/minidown/issues>

License MIT + file LICENSE

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Imports htmltools, katex, knitr, mime, rmarkdown, sass, xfun

Suggests callr, dplyr, purrr, shiny, testthat (>= 2.1.0), tidyr, tibble

SystemRequirements pandoc (>= 2.7.2) - <http://pandoc.org>

VignetteBuilder knitr

Repository <https://atusy.r-universe.dev>

RemoteUrl <https://github.com/atusy/minidown>

RemoteRef HEAD

RemoteSha 519b8bc9a5edc6aedc1f951938c8bde1fb22b5d8

Contents

| | |
|-------------------------------|---|
| download_rmd_button | 2 |
| frameworks | 3 |
| mini_document | 3 |

| | |
|--------------|----------|
| Index | 6 |
|--------------|----------|

| | |
|---------------------|---|
| download_rmd_button | <i>Generate an HTML widget to download input Rmd file</i> |
|---------------------|---|

Description

The button can self-contain the input data by base64 encoding.

Usage

```
download_rmd_button(
  input = NULL,
  text = "Download Rmd",
  ...,
  class = "button",
  align = "right",
  aside = TRUE,
  embed = NULL
)
```

Arguments

| | |
|-------|---|
| input | Filename of the input. If NULL, the function automatically detects the name of the knitting Rmd file. |
| text | The text for the hyperlink. |
| ... | Arguments passed to the embed function. |
| class | HTML class(es) given to the anchor element generated by embed (default: "button"). |
| align | Align the button by CSS's text-align attribute. This feature is disabled when aside is FALSE |
| aside | Whether to wrap the anchor element by the aside element. |
| embed | A function to embed file(s). One of xfun::embed_file, xfun::embed_files, or xfun::embed_dir. |

Value

shiny.tag class object.

Examples

```

set.seed(1L)

input <- tempfile()
writeLines("", input)
download_rmd_button(input)

# Requires zip command
if (interactive()) {
  input <- tempdir()
  download_rmd_button(input, embed = xfun::embed_dir)
}

```

frameworks

Lightweight CSS frameworks meta data

Description

To see the names of the frameworks, run `names(frameworks)`. To see the names of themes of a framework, say "mini", run `names(frameworks$mini$stylesheet)`

Usage

```
frameworks
```

Format

A list

mini_document

Convert to an HTML document powered by the lightweight CSS framework.

Description

The output format is HTML5 in general. If `framework = "bootstrap"` is given, the output format becomes HTML4 and comparable to `rmarkdown::html_document` except for the behavior of the `code_folding` option.

Usage

```

mini_document(
  framework = "sakura",
  theme = "default",
  toc = FALSE,
  toc_float = FALSE,
  toc_highlight = FALSE,
  section_divs = TRUE,
  code_folding = c("none", "show", "hide"),
  results_folding = c("none", "show", "hide"),
  tabset = FALSE,
  code_download = FALSE,
  self_contained = TRUE,
  math = "katex_serverside",
  template = "default",
  extra_dependencies = NULL,
  includes = list(),
  keep_md = FALSE,
  pandoc_args = NULL,
  ...
)

```

Arguments

| | |
|------------------|--|
| framework, theme | A string to specify the name of a framework (default: "sakura") and its theme (default: "default"). Note that theme = "default" is a special keyword which selects a theme defined as default internally. See frameworks for available light weight CSS frameworks and their themes. If you want to scratch styles by yourself, use framework = "none". |
| toc | TRUE to include a table of contents in the output |
| toc_float | TRUE to float the table of contents to the left of the main document content. |
| toc_highlight | This is an experimental feature. TRUE highlights the table of contents according to the browser's viewport. |
| section_divs | Wrap sections in <div> tags, and attach identifiers to the enclosing <div> rather than the header itself. |
| code_folding | Setup code folding by a string or a named list. A choice for the string are "none" to disable, "show" to enable and show all by default), and "hide" to enable and hide all by default. If a named list, each element may have one of the above strings. Names are some of "source", "output", "message", "warning", and "error". If the list does not have some of the element with the above name, they are treated as "none". |
| results_folding | Setup results folding by a string, "none", "show", or "hide". This feature will fold entire results, including side effects such as figures and tables. |
| tabset | TRUE converts sections to tabs if they belong to the tabset-class section. The tabs inherit names from the corresponding sections. Unlike rmarkdown::html_document, |

the tabs can be navigated by table of contents, and can be shared by unique URLs. Note that `framework = "bootstrap"` falls back to the native feature of `rmarkdown::html_document`. This feature also requires `section_divs = TRUE`.

| | |
|---------------------------------|---|
| <code>code_download</code> | If <code>TRUE</code> and <code>framework = "bootstrap"</code> , the output includes Rmd file itself and supplies download button of it. |
| <code>self_contained</code> | Produce a standalone HTML file with no external dependencies, using data: URIs to incorporate the contents of linked scripts, stylesheets, images, and videos. Note that even for self contained documents MathJax is still loaded externally (this is necessary because of its size). |
| <code>math</code> | This is a good choice when you want to exclude JavaScript from the output. The default value <code>"katex"</code> attempts client-side rendering, but falls back to server-side rendering, i.e. <code>"katex_serverside"</code> , when runtime is <code>shiny</code> or <code>shiny_prerendered</code> . Otherwise, if the <code>framework</code> is <code>"bootstrap"</code> , this option is passed to the <code>mathjax</code> argument of <code>rmarkdown::html_document</code> . |
| <code>template</code> | Pandoc template. If <code>"default"</code> , the package's internal template is used. If a path, user's original template is used. If <code>NULL</code> , pandoc's internal template is used. |
| <code>extra_dependencies</code> | Additional function arguments to pass to the base R Markdown HTML output formatter <code>html_document_base</code> |
| <code>includes</code> | Named list of additional content to include within the document (typically created using the <code>includes</code> function). |
| <code>keep_md</code> | Keep the markdown file generated by knitting. |
| <code>pandoc_args</code> | Additional command line options to pass to pandoc |
| <code>...</code> | Arguments passed to <code>rmarkdown::html_document</code> |

Examples

```
## Not run:
library(rmarkdown)
library(minidown)
render("input.Rmd", mini_document)

## End(Not run)
```

Index

* **datasets**

frameworks, [3](#)

download_rmd_button, [2](#)

frameworks, [3](#)

html_document_base, [5](#)

includes, [5](#)

mini_document, [3](#)